

Unica 4/r



Unica 8/r



TECHNICAL INFORMATION

- **Models available:**

Unica 4/r Refrigerated (4 bottles in line)

Unica 8/r Refrigerated (8 bottles in line)

- **Bottle compartment temperature:**

4/r 6-18°C

8/r 6-18°C / 12-18°C

- **Refrigeration:**

Alternative compressor

Ultra-silent operation

Low energy consumption

- **Bottles:**

Quick loading with gas spring

Loading with self-centring system

Complete bottle visibility

- **Gas supply**

Food grade nitrogen E941 or Food grade argon E938

- **Supply pressure control:**

Dispenser inlet

Dispensing

- **Wine maintenance:**

Separate for each bottle

- **Doses:**

Up to 3 configurable doses for each bottle

- **System use and activation:**

Behind bar (without wine card)

Self-service (with wine card)

- **Card reader:**

SLE4442 chip

RFID ISO/IEC14443A/B (MIFARE)

- **Display:**

Touchscreen

7" colour LCD

Brightness 800cd

Side viewing angle of 140°

- **Lighting:**

Internal cool white LED (4000K)

External cool white LED (4000K)

- **Data connection:**

LAN

WIFI

- **Door:**

Insulated glazing with magnetic closure

Assisted tilt system

Key lock

- **Materials:**

Stainless steel

Coloured stainless steel

Glass

- **Optional accessories:**

Canister

Regulators for cylinders

Angulars finishing

2+2 bottle dividing panel
(for model 4/r only)




Customisations on request.


Models	L	H	P	Weight	Electrical requirements
Unica 4/r	53,1 cm 20,91 in	70,4 cm 27,72 in	31,7 cm 12,48 in	37 kg 81,57 lb	100-240 V 50-60 Hz 120 W (depending on the target market)
Unica 8/r	95,1 cm 37,44 in	70,4 cm 27,72 in	31,7 cm 12,48 in	57,5 kg 126,77 lb	100-240 V 50-60 Hz 125 W (depending on the target market)




EXAMPLES OF MODULAR COMPOSITIONS




4 Dispensers
+
4 Angular




5 Dispensers
+
5 Angular




6 Dispensers
+
6 Angular



4 Dispensers
+
4 Angular



2 Dispensers
+
2 Angular



3 Dispensers
+
3 Angular